

PMC SERIES CONNECTOR

The **1/8" flow PMC coupling** covers a wide variety of general-purpose applications. Featuring the CPC thumb latch, the PMC is easier to use than ball-and-sleeve designs. One-hand connection/disconnection and integral terminations make the PMC the choice for ease of use and manufacture. This coupling is NuSeal® compatible.



SPECIFICATIONS

PRESSURE:

Vacuum to 120 psi, 8.3 bar

TEMPERATURE:

-40°F to 180°F (-40°C to 82°C)

MATERIALS:

Main components and valves: Acetal

Thumb latch: Stainless steel

Valve spring: 316 stainless steel

External springs and pin: Stainless steel

O-rings: Buna-N

COLOR:

Natural white, others available

TUBING SIZES:

1/16" to 1/4" ID, 1.6 mm to 6.4 mm ID

WARNING: Pressure, temperature, chemicals, and operating environment can affect the performance of couplings. It is the customer's responsibility to test the suitability of CPC products in their own application conditions.

FEATURES

Hose barb shroud

Integral terminations

Compatible

Clicks when connected

BENEFITS


Extra protection for the 1/16" hose barb

Fewer leak points, shorter assemblies, faster installations


Mates with PMC12 and MC Series couplings (see pages 34 and 38)

Assurance of a reliable connection


PMC AIR FLOW • 100 psig inlet pressure



PMC Pressure Range



PMC WATER FLOW



These graphs are intended to give you a general idea of the performance capabilities of each product line. The shaded area of each graph represents the operating range of the product family, i.e., upper and lower values are shown. Therefore, depending on the exact coupling configurations selected, you can reasonably expect values to fall within the shaded area.



cpcworldwide.com/PMC



COLDER PRODUCTS COMPANY®

U.S.A.

PHONE: +1 (651) 645-0091

TOLL FREE: +1 (800) 444-2474

E-MAIL: info@cpcworldwide.com

COLDER PRODUCTS COMPANY GMBH

Germany

E-MAIL: cpcgmbh@cpcworldwide.com

DOVER (SHANGHAI) INDUSTRIAL CO., LTD

ShangHai, China

PHONE: +86 21 2411 2666

TOLL FREE: +86 400 990 1978

E-MAIL: asiapacific@cpcworldwide.com

[illegible]


PMC SERIES DIMENSIONS

COUPLING BODIES - Acetal

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ	STRAIGHT THRU	SHUTOFF	A	B
	IN-LINE PIPE THREAD	1/8" NPT		PMC1002	PMCD1002	0.79 (20.1)	1 (25.4)
		1/8" BSPT		PMC1002BSPT	PMCD1002BSPT	0.79 (20.1)	1 (25.4)
		1/4" NPT		PMC1004	PMCD1004	0.79 (20.1)	1.1 (27.9)
		1/4" BSPT		PMC1004BSPT	PMCD1004BSPT	0.79 (20.1)	1.1 (27.9)
	PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF†		4.0 mm OD, 2.0 mm ID	PMC12M42	PMCD12M42	0.77 (19.6)	1.65 (41.9)
		5/32" OD, 0.10" ID	4.0 mm OD, 2.5 mm ID	PMC12025	PMCD12025	0.77 (19.6)	1.7 (43.2)
		1/4" OD, 0.17" ID	6.4 mm OD, 4.3 mm ID	PMC1204	PMCD1204	0.77 (19.6)	1.72 (43.7)
	PANEL MOUNT HOSE BARB	1/16" ID	1.6 mm ID	PMC1601	PMCD1601	0.77 (19.6)	1.4 (35.6)
		1/8" ID	3.2 mm ID	PMC1602	PMCD1602	0.77 (19.6)	1.65 (41.9)
		3/16" ID	4.8 mm ID	PMC1603	PMCD1603	0.77 (19.6)	1.85 (47.0)
		1/4" ID	6.4 mm ID	PMC1604	PMCD1604	0.77 (19.6)	1.85 (47.0)
	PANEL MOUNT FEMALE THREAD	10-32 UNF		PMC181032	PMCD181032	0.77 (19.6)	1.25 (31.8)
	IN-LINE FERRULELESS POLYTUBE FITTING, PTF†		4.0 mm OD, 2.0 mm ID	PMC13M42	PMCD13M42	0.81 (20.6)	1.65 (41.9)
		5/32" OD, 0.10" ID	4.0 mm OD, 2.5 mm ID	PMC13025	PMCD13025	0.81 (20.6)	1.65 (41.9)
		1/4" OD, 0.17" ID	6.4 mm OD, 4.3 mm ID	PMC1304	PMCD1304	0.81 (20.6)	1.75 (44.5)
	IN-LINE HOSE BARB	1/16" ID	1.6 mm ID	PMC1701	PMCD1701	0.81 (20.6)	1.41 (35.81)
		1/8" ID	3.2 mm ID	PMC1702	PMCD1702	0.81 (20.6)	1.45/1.65 (36.8/41.9)
		3/16" ID	4.8 mm ID	PMC1703	PMCD1703	0.81 (20.6)	1.65/1.85 (41.9/47.0)
		1/4" ID	6.4 mm ID	PMC1704	PMCD1704	0.81 (20.6)	1.65/1.85 (41.91/47.0)
	IN-LINE FEMALE THREAD	10-32 UNF		PMC191032	PMCD191032	0.81 (20.6)	1.25 (31.8)

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. †NOTE: CPC™ Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.


PRODUCT DIMENSIONS



- A = Height/Diameter
- B = Total Length
- D = Elbow Radial Length

PANEL DIMENSIONS

	PANEL OPENING	PANEL THICKNESS MAX. – MIN.	PANEL NUT HEX	PANEL NUT THREAD
COUPLING BODIES	see drawing	0.50 – 0.05	5/8	1/2-24UNS
COUPLING INSERTS	1/2	0.30 – 0.05	5/8	1/2-24UNS



COUPLING INSERTS - Acetal

	TERMINATION	TUBING/THREAD SIZE	METRIC EQ	STRAIGHT THRU	SHUTOFF	A	B	D
	IN-LINE PIPE THREAD	1/8" NPT		PMC2402	PMCD2402	0.58 (14.7)	1.03/1.45 (26.2/36.8)	
		1/8" BSPT		PMC2402BSPT	PMCD2402BSPT	0.58 (14.7)	1.03/1.44 (26.2/36.6)	
		1/4" NPT		PMC2404	PMCD2404	0.65 (16.5)	1.13/1.42 (28.7/36.1)	
		1/4" BSPT			PMCD2404BSPT	0.65 (16.5)	1.13/1.42 (28.7/36.1)	
	PANEL MOUNT FERRULELESS POLYTUBE FITTING, PTF† (NON-VALVED SHOWN)	1/4" OD, 0.17" ID	6.4 mm OD, 4.3 mm ID	PMC4004	PMCD4004	0.72 (18.3)	1.70/1.82 (43.2/46.2)	
	PANEL MOUNT HOSE BARB	1/16" ID	1.6 mm ID	PMC4201	PMCD4201	0.72 (18.3)	1.38/1.50 (35.1/38.1)	
		1/8" ID	3.2 mm ID	PMC4202	PMCD4202	0.72 (18.3)	1.63/1.75 (41.4/44.5)	
		3/16" ID	4.8 mm ID	PMC4203	PMCD4203	0.72 (18.3)	1.83/1.95 (46.5/49.5)	
		1/4" ID	6.4 mm ID	PMC4204	PMCD4204	0.72 (18.3)	1.83/1.95 (46.5/49.6)	
	IN-LINE FERRULELESS POLYTUBE FITTING, PTF†		4.0 mm OD, 2.0 mm ID	PMC20M42	PMCD20M42	0.58 (14.7)	1.08/1.60 (27.4/40.6)	
		5/32" OD, 0.10" ID		PMC20025	PMCD20025	0.58 (14.7)	1.13/1.65 (28.7/41.9)	
		1/4" OD, 0.17" ID	4.0 mm OD, 2.5 mm ID	PMC2004	PMCD2004	0.58 (14.7)	1.15/1.57 (29.2/39.9)	
		3/8" OD, 0.25" ID		PMC2006	PMCD2006	0.65 (16.5)	1.40/1.52 (35.6/38.6)	
	IN-LINE HOSE BARB (NON-VALVED SHOWN)		6.4 mm OD, 4.3 mm ID					
		1/16" ID	1.6 mm ID	PMC2201	PMCD2201	0.5 (12.7)	0.80/1.47 (20.3/37.3)	
		1/8" ID	3.2 mm ID	PMC2202	PMCD2202	0.5 (12.7)	1.00/1.67 (25.4/42.4)	
		3/16" ID	4.8 mm ID	PMC2203	PMCD2203	0.5 (12.7)	1.20/1.88 (30.5/47.8)	
	IN-LINE FEMALE THREAD	1/4" ID	6.4 mm ID	PMC2204	PMCD2204	0.5 (12.7)	1.22/1.70 (31.0/43.2)	
		10-32 UNF		PMC281032	PMCD281032	0.58 (14.7)	0.63/1.31 (16.0/33.3)	
	ELBOW FERRULELESS POLYTUBE FITTING, PTF†	5/32" OD, 0.10" ID	4.0 mm OD, 2.5 mm ID	PMC21025		0.5 (12.7)	1.17 (29.7)	0.75 (19.1)
		1/4" OD, 0.17" ID		PMC2104	PMCD2104	0.5 (12.7)	1.17/1.21 (29.7/30.7)	0.77 (19.6)
			6.4 mm OD, 4.3 mm ID					
	ELBOW HOSE BARB (NON-VALVED SHOWN)							
		1/8" ID	3.2 mm ID	PMC2302	PMCD2302	0.5 (12.7)	0.85/1.21 (21.6/30.7)	0.75/0.69 (19.1/17.5)
		1/4" ID	6.4 mm ID	PMC2304	PMCD2304	0.5 (12.7)	1.00/1.21 (25.4/30.7)	0.95/0.90 (24.1/22.9)

All measurements are in inches (mm) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted. †NOTE: CPC™ Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

All measurements are in inches (millimeters) unless otherwise noted. Tubing must meet stated inside and outside diameters. Couplings are pictured with valves unless otherwise noted. †NOTE: CPC™ Ferruleless PTF (polytube fitting) terminations do not require ferrules to achieve a secure connection and are therefore easier to use and reuse. PTF fittings are designed for semi-rigid tubing, i.e., polyethylene, nylon, polyurethane, etc.

NSF

NSF OPTION AVAILABLE

This product has an NSF compatible product for food applications. Our food-grade couplings are superior to general fittings for fluid control because they incorporate built-in shutoff valves, enabling tubing to be disconnected without having to turn off the water supply. Scan the QR code to be taken to the NSF specific product web page.



WARRANTY: All sales are subject to the Colder Products Company® limited express warranty set forth in the CPC catalog. Contact your local distributor or CPC Customer Service for warranty provisions.

Warning: Due to the wide variety of possible fluid media and operating conditions, unintended consequences may result from the use of this product, all of which are beyond the control of CPC. It is the user's responsibility to carefully determine and test for compatibility for use with their application. All such risks shall be assumed by the buyer.

COPYRIGHT © 2026 BY COLDER PRODUCTS COMPANY.

CPC, Colder Products Company, and Colder Products are registered trademarks with the United States Patent and Trademark Office.

For detailed trademark information, please visit: <https://www.cpcworldwide.com/Trademarks>

CAT2021-PMC REV 4/26